

SATIN FINISH SURFACE WAX



Satin Finish Surface Wax

Water based satin effect finishing wax For interior use

Water based finishing wax. For interior use.

Enhances appearance and further protects surfaces that are impregnated with Ecoprotec Natural Finish Stone Sealer or Ecoprotec Colour Enhancing Stone Sealer. Self polishing or can be polished to restore or increase shine. Ideal for both treatment and aftercare. For all types of unpolished natural and artificial stone, encaustics, decorative concrete toppings, vitrified quarry tiles and machine made terracotta.

Directions for use

Preparation: Ensure surface to be treated is completely clean and dry. Retained moisture may cause the Satin Finish Surface Wax to dry opaque or prevent the seal from reaching full hardness.

Application:

Rough cut, textured or riven surfaces - Use a paint brush. Apply a thin coat evenly in one direction. Do not rub or buff. Allow to dry (1hr min) Apply further coats at right-angles to previous until an even film is created (max 6 coats).

Honed and smooth surfaces – Apply using a micro-fibre cloth or pad. Pour contents into a flat tray container. Soak up the solution with cloth or pad and apply thinly and evenly to the surface. Apply further coats at right angles to previous until an even film is created (max 6 coats) Do not over apply as too many coats may cause unsightly build up and/or reduce the efficiency of the product. Begins to harden after an hour, but will take a further 3 days to become fully water resistant. If in doubt, experiment on spare tiles to establish the correct method of application and optimum number of coats before general use.

Coverage: M² per coat

	1 LTR	5 LTR	
Smooth & Honed	30m²	150m²	
Textured and Riven	20m²	100m²	

Aftercare

Routinely sweep the floor. Use Ecoprotec Natural Stone and Porcelain Aftercare Cleaner to clean and protect treated surfaces. In areas where the seal becomes worn, apply more Ecoprotec Satin Finish Surface Wax.

At some stage, complete renovation of the seal may be desired. In this case use **Ecoprotec Stone & Tile Intensive Cleaner** to strip the original seal before re-sealing..

Storage information

Store in a cool, dry, frost free environment Shelf life up to 4 years

Other

Avoid shaking the bottle prior to use. Frothing of liquid may lead to an inconsistent finish. Store in a frost proof place. Avoid extremes of temperature. Do not use below freezing. If in doubt, test on an inconspicuous area prior to general application. Avoid using strong detergents to wash treated surfaces. On higher porosity floor materials Ecoprotec Natural Finish Stone Sealer or Ecoprotec Colour Enhancing Stone Sealer may be required prior to use of Ecoprotec Satin Finish Surface Wax. Caution: Not recommended for use on outdoor surfaces or in damp environments and where water remains (bathrooms, showers).

Health, Safety & Environmenta

Contains:1,2-BENZISOTHIAZOL-3(2H)-ONE

May produce an allergic reaction. Causes serious eye irritation. Keep out of reach of children. Do not get in eyes, on skin or on clothing. Wear protective gloves/protective clothing/eye protection/face protection.

IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.



WARNING



This information is offered without quarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area



