

CLEANING SEALING & AFTERCARE

BOILED LINSEED OIL IMPREGNATING SEALER TECHNICAL DATA SHEET

REF: 11/5/2 MARCH 2017



LTP BOILED LINSEED OIL

Impregnating Sealer.

Interior use only.

Traditional sealer for terracotta.

For protecting and enhancing machine and hand made terracotta. Fills and hardens within the open pores of the terracotta inhibiting the absorption of grime and fluids. Offers good mechanical strength to low fired handmade terracotta.

IMPORTANT: Do not let the oil oxidise on the surface of the tile. Remove any unabsorbed surplus within one hour of the application using a clean cloth and, if necessary, a little Genuine Turpentine. Experiment on spare tiles to establish the number of coats required to achieve full saturation.

Directions for use

For application and cleaning tools see LTP website.

Apply by brush a coat at a time until the tiles are saturated. Allow at least 12 hours between each coat to ensure that the oil thoroughly oxidises. Most Terracotta will take one or two coats to reach saturation, while others, particularly some of hand made terracotta, may take as many as four or five coats. Leave the final coat to dry for at least 24 hours before polishing with LTP Clear or Antique Wax or finishing with LTP Ironwax Gloss or Satin.

Coverage

Medium Porosity Terracotta: 1-2 litres per 10m²
Higher Porosity Terracotta: 3-4 litres per 10m²

Storage information

Store in a cool, dry, frost-free environment.

Shelf Life – Up to 4 years for un-opened containers

Health, Safety & Environmental

Keep out of the reach of children.

Do not drink.

Keep/Store away from clothing/combustible materials.

Store in a closed container.

Dispose of contents/container to hazardous waste collection point.

May cause minor irritation on skin contact.

May cause minor irritation on eye contact.

Label in Accordance With (EC) No 1272/2008

DO NOT LEAVE SOILED APPLICATION CLOTHS WHERE THEY MAY CONSTITUTE A FIRE RISK, AS THEY ARE LIABLE TO SPONTANEOUS COMBUSTION.

Important:

All rags and cloths used should be immediately burnt, or if this is not possible soaked in soapy water before disposing of in a bin. The application cloths should never be crumpled up into a ball.



This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area.



For any LTP product information call our technical helpline
+44 (0) 1823 666213 | www.ltp-online.co.uk | info@ltp-online.co.uk
Tone Estate, Milverton Road, Wellington, Somerset, TA21 0AN UK



Federation
Stone
Great Britain

